
CASAR PLASTIC COVERED ROUND BALANCE ROPES

- Koepe Tail / Balance Rope
- · Conventional strands
- Rotation resistant
- · Designed to have a specific unit weight
- Impregnated and coated with tough polymer, offering superior protection against the harsh, aggressive environment of an underground mining shaft.
- Available in ordinary (regular) lay or langs lay



PROPERTIES









Lubricated

Plast rope

APPLICATIONS

Our proven and reliable plastic impregnated and coated round rope is perfectly designed to operate as a balance (tail) rope on a koepe friction winder application. The tough polymer provides a superior protection against the harsh, aggressive environment of an underground mining shaft.



| Inner, nominal diameter | | Outer, nominal dia- meter | | Weight | | Minimum Breaking Force | | |
|----------------------------|----|------------------------------|----|---------|-------|---------------------------|------|---------|
| | mm | inch | mm | inch | kg/m | lb/ft | kN | lbs |
| | 30 | 1 3/16 | 37 | 1 7/16 | 3.65 | 2.45 | 467 | 105,000 |
| | 32 | 1 1/4 | 38 | 1 1/2 | 4.84 | 3.25 | 512 | 115,000 |
| | 33 | 1 5/16 | 40 | 1 9/16 | 5.13 | 3.45 | 534 | 120,000 |
| | 35 | 1 3/8 | 41 | 1 5/8 | 5.71 | 3.84 | 649 | 146,000 |
| | 37 | 1 7/16 | 43 | 1 11/16 | 6.10 | 4.10 | 734 | 165,000 |
| | 40 | 1 9/16 | 46 | 1 13/16 | 7.10 | 4.77 | 823 | 185,000 |
| | 41 | 1 5/8 | 48 | 1 7/8 | 7.89 | 5.30 | 912 | 205,000 |
| | 43 | 1 11/16 | 49 | 1 15/16 | 8.14 | 5.47 | 979 | 220,000 |
| | 44 | 1 3/4 | 51 | 2 | 8.75 | 5.88 | 1032 | 232,000 |
| | 48 | 1 7/8 | 54 | 2 1/8 | 10.04 | 6.75 | 1192 | 268,000 |
| | 51 | 2 | 57 | 2 1/4 | 11.43 | 7.68 | 1352 | 304,000 |
| | | | | | | | | |

Product specifications are subject to change without notice or obligation. The shown drawings or cross sections are only for illustrative purposes: the images can vary depending on requested diameter and current status of technical development. This table is for reference only. Additional sizes available upon request.